

DETAILS

- + compact table device
- + double sealing (top/bottom)
- + ejector vacuum pump (requires comporessed air)
- + vacuum generation: sensor and time control
- + re-gassing device
- + saving of up to 4 programs
- + incl. emergency stop
- + incl. acryl protection cover



K-TECH Electronic Vertriebs GmbH

Fritz-Hopf-Straße 11a 86720 Nördlingen, Germany

Telefon: +49 (0) 9081 27590-0 E-Mail: info@k-techgmbh.de

www.k-techgmbh.com





Tape & Reel



VACUUM SEALER AZ SERIES





Our AZ series vacuum sealers are particularly suitable for processing multilayer composite bags.

Depending on the bag, the vacuum-packed products are protected from moisture, dirt, external influences and direct discharge.

The AZ series devices are equipped with a suction nozzle and therefore do not require a chamber. Thus, you are not restricted in the length of the bags and the bags are vacuumed in a short time using the Venturi valve.



TECHNICAL DATA

Technical details AZ450	
Type / size	AZ450
Sealing bar length	450 mm
Sealing bar width	10 mm
Vacuum pump	ejector vacuum pump
Electrial connection	230 V / 50-60 Hz
Electrical power	3.2 kW
Compressed air	5 - 7 bar
Max. vacuum	са. 80 Кра
Vacuum generation	time controlled vacuum sensor controlled
Re-gassing device	time controlled
Vacuum display	LCD-display
Housing and shelf	stainless steel
Protective cover	acryl

Dimensions	
Length x width x height	839 x 506 x 284 mm
Weight	ca. 37 kg

Other sizes	
AZ600	sealing bar length 600 mm
AZ800	sealing bar length 800 mm
AZ1000	sealing bar length 1'000 mm
AZ1200	sealing bar length 1'200 mm